

LOTOXANE® FAST WIPES

Convenient and versatile degreasing wipes impregnated with Lotoxane® Fast



Lint free wipes impregnated with a highly refined solvent blend offering a combination of low odour excellent degreasing power and minimal residue on drying. Due to the high solvent purity, Lotoxane Fastwipes provide a safer alternative to the most hazardous solvents used throughout Industry. Lotoxane Fastwipes therefore provide convenient portable solution for use on the most sensitive metals and plastics and in critical applications as well as for general oil and grease removal.

ADVANTAGES

Flashpoint 40°C

Approved by aerospace manufacturers

Wipe format reduces risk of spillage and reduces solvent vapour in use

TYPICAL APPLICATIONS

- Wipe degreasing of general surfaces, components or tools.
- Wipe-cleaning prior to painting, bonding and removing protective coatings.
- Suitable for use as Stage 1 – Cleaner in NDT (Non Destructive Testing) processes

APPLICATION INSTRUCTIONS

General

Wipe over surface to remove oil and grease residues and allow to air dry.

NDT-Stage 1, and critical cleaning

1. Withdraw one wipe and reseal container.
2. Wipe the area, refolding after each pass to expose uncontaminated cloth.
3. Repeat operations 2 and 3 until 3 consecutive passes show no visible signs of contamination.
4. Allow to dry.

LOTOXANE® FAST WIPES

Convenient and versatile degreasing wipes impregnated with Lotoxane® Fast



TECHNICAL DATA

ABSORPTION CAPACITY	360%
ODOUR	Mild
SOLUBILITY	Insoluble in water
RELATIVE DENSITY	0.75 @ 15 °c
FLASH POINT (°C)	40 P/M Pensky-Mar
MULLEN BURST	300 kPa
FLAMMABILITY LIMITS LOWER (%) / UPPER (%)	0.60 / 6.5
BASIC WEIGHT	68 gsm
PACK SIZE	10 x 85 Wipes Carton

PRECAUTIONS

Keep away from heat, sparks and open flame.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



LOTOXANE® FAST

A faster drying Lotoxane® variant which evaporates three times faster than standard Lotoxane®



LOTOXANE®

Safe high flash point degreaser



WORKSHOP WIPES

Effective removal of semi-cured adhesives & sealants, lacquers, resins and inks



QED

Quick dry electrical & workshop degreaser



ISO 14001:2004
Cert No. 1263



OHS 536783



Q 05320



Cert: 310314001