

SUPER SLAKS

Penetrating fluid with graphite



SUPER SLAKS aerosol Super Slaks' unique penetrating action aids dismantling of any seized or corroded bolts, nuts, components or assemblies. A combination of fast penetrating solvents and low viscosity oils utilise capillary action to rapidly penetrate tight and corroded threads. This reduces release torque, aids dismantling of components and prevents damage to nuts bolts studs and threads.

ADVANTAGES

Rapidly penetrates corroded and seized, nuts, bolts and studs, easing release and preventing shearing

Contains mineral oils, oxidised waxes and colloidal graphite

Powerful heavy duty release agent

Suitable for use in mechanical, maintenance and repair applications

Film remains effective up to 150°C

TYPICAL APPLICATIONS

- Ideal for use in all areas to aid routine maintenance and repair of components, machinery, vehicles, plant and heavy equipment
- Suitable for use on most metals
- Super Slaks can be used on tight or corroded nuts and bolts, studs, linkages, splines, tapered shafts, hinges, bearings, farm and industrial equipment etc

APPLICATION INSTRUCTIONS

Do not spray onto hot surfaces or in the vicinity of naked flames or other sources of ignition.
 Spray liberally onto affected components and allow to penetrate. For optimum penetration position the component to reduce run off and to allow gravity to aid penetration.
 Suitable penetration is normally achieved in one minute but for large or very tightly seized threads allow up to 10 minutes contact time.
 Use tightening movement to crack rust, then release.

SUPER SLAKS

Penetrating fluid with graphite



TECHNICAL DATA

APPEARANCE	Grey/Black fluid
ODOUR	Solvent
SOLUBILITY	Insoluble in water
FLASHPOINT (°C) (CONC)	-10 CC (Closed cup)
SG (CONC)	0.86
PROPELLANT	Hydrocarbon
PACK SIZE	600ml Aerosol

PRECAUTIONS

Keep away from heat, sparks and open flame. Avoid inhalation of vapours/spray and contact with skin and eyes. Provide good ventilation.

STORAGE PRECAUTIONS

Store at moderate temperatures in a dry well ventilated area. Keep between 0 and 40°C.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



SEIZE EEZE

High temperature anti seize lubricant



BRITOX PLUS

High strength descaler, concrete and rust remover



RUST REMOVER 28

Mild rust and scale remover



ISO 14001:2004
Cert No. 1263



OHS 536783



Q 05320



Cert: 310314001