## **LOTOXANE® TRIPLE F**

A faster drying Lotoxane® variant which evaporates 15 times faster than standard Lotoxane®





LOTOXANE® TRIPLE F is a high quality solvent degreaser that offers professional users a versatile fast evaporating alternative to more hazardous products.

#### **ADVANTAGES**

Low odour

Reduced hazard to user

Helps in reducing VOCs'

Rapid evaporation

#### **TYPICAL APPLICATIONS**

- Removal of oils, greases, machining fluids and general contamination in manufacturing process
- → Pre cleaning prior to NDT or inspection
- Removal of temporary protective coatings/dewaxing; Cleaning prior to painting or bonding operations
- Degreasing of machinery, components and assemblies during maintenance and repair
- Cleaning electrical and electronic equipment
- → De-watering components and electrical systems

### **APPLICATION INSTRUCTIONS**

**Manual Cleaning**: Apply to the surface by spray or paintbrush. Agitate stubborn deposits if required with a stiff brush and wipe away residues with a clean cloth.

**Dip tank**: Allow adequate contact time, typically 10 - 15 minutes, then remove and allow to drain, agitate components if required. To reduce losses from the tank it is advised that a close fitting lid is used.

Parts washers: Cold use only. Leave components to air dry naturally.

**Note**: Drying times can be improved by wiping away excess or forced air drying.

## **LOTOXANE® TRIPLE F**

A faster drying Lotoxane® variant which evaporates
15 times faster than standard Lotoxane®



### **TECHNICAL DATA**

ODOUR	Low odour
SOLUBILITY	Insoluble in water
FLAMMABILITY	Flammable liquid and vapour
FLASH POINT	7°C
PACK SIZES	<ul><li></li></ul>

Other pack sizes available on a made to order basis.

### **LIMITATIONS**

Not suitable for vapour degreasing. For heavier duty applications consider Lotoxane HD or Fastklean.

# HEALTH AND SAFETY, STORAGE AND PRECAUTIONS

Refer to Safety Data Sheet (available on request)

### **ALSO AVAILABLE**



**LOTOXANE®**Safe non-flammable solvent degreaser.



**LOTOXANE® FAST**A faster drying Lotoxane® variant which evaporates 3 times faster than standard



LOTOXANE® XF
A faster drying Lotoxane® variant
which evaporates 6 times faster than
standard Lotoxane®.



LOTOXANE® HD
Safe non-flammable solvent degreaser
with enhanced degreasing ability.



ISO 14001:2004 Cert No. 1263



OHS 536783













