LOTOXANE® XF

A faster drying Lotoxane® variant which evaporates 6 times faster than standard Lotoxane®





LOTOXANE® XF is a high quality solvent degreaser that offers professional users a versatile alternative to more hazardous products. It is widely approved by major OEMs for production and maintenance cleaning.

ADVANTAGES

PBCA aerosol limits environmental impact



Reduced hazard to user

Helps in reducing VOCs'

TYPICAL APPLICATIONS

- Removal of oils, greases, machining fluids and general contamination in manufacturing process
- → Pre cleaning prior to NDT or inspection
- Removal of temporary protective coatings/dewaxing; Cleaning prior to painting or bonding operations
- Degreasing of machinery, components and assemblies during maintenance and repair
- ▼ Cleaning electrical and electronic equipment
- → De-watering components and electrical systems

APPLICATION INSTRUCTIONS

Manual Cleaning: Apply to the surface by spray or paintbrush. Agitate stubborn deposits if required with a stiff brush and wipe away residues with a clean cloth.

Dip tank: Allow adequate contact time, typically 10 - 15 minutes, then remove and allow to drain, agitate components if required. To reduce losses from the tank it is advised that a close fitting lid is used.

Parts washers: Cold use only. Leave components to air dry naturally.

Note: Drying times can be improved by wiping away excess or forced air drying

LOTOXANE® XF

A faster drying Lotoxane® variant which evaporates 6 times faster than standard Lotoxane®



TECHNICAL DATA

ODOUR	Low odour
SOLUBILITY	Insoluble in water
FLAMMABILITY	Flammable liquid and vapour
FLASH POINT	27°C
PACK SIZES	 ▼ 500ml aerosol ▼ 5 litre ▼ 20 litre ▼ 210 litre

Other pack sizes available on a made to order basis.

HEALTH AND SAFETY, STORAGE AND PRECAUTIONS

Refer to Safety Data Sheet (available on request)

LIMITATIONS

Not suitable for vapour degreasing. For heavier duty applications consider Lotoxane HD or Fastklean. When faster evaporation is required consider Lotoxane Triple F.

ACCREDITATIONS & REGISTRATIONS

- → Rolls Royce CSS255 Type A,B,D
- → Rolls Royce OMAT 1/257H

ALSO AVAILABLE



LOTOXANE®Safe non-flammable solvent degreaser.



LOTOXANE® FAST
A faster drying Lotoxane® variant which evaporates 3 times faster than standard



LOTOXANE® TRIPLE FA faster drying Lotoxane® variant which evaporates 15 times faster than standard Lotoxane®.



LOTOXANE® HD
Safe non-flammable solvent degreaser
with enhanced degreasing ability.



ISO 14001:2004 Cert No. 1263



OHS 536783













