

# OXALWASH

Train exterior wash optimised for removal of iron staining



**OXALWASH AUTOSHINE contains a synergistic blend of oxalic acid, surfactants and shine enhancing agents to clean and restore trains carriages and other rolling stock.**

**Removing dirt, oil and rust in one application.**

## ADVANTAGES

Oxalwash Autoshine contains surface active agents to rapidly remove dirt oil and grime from surfaces.

Oxalic acid dissolves brake/iron dust particles and removes iron stains from paintwork, vinyl and glass.

Rinses freely, with no scale residues associated with typical oxalic acid based cleaners.

Contains no mineral acids minimizing damage to concrete sleepers, floors and mortar.

Enhances shine on new or dulling paintwork, vinyl coatings and glass.

Will not damage glass.

Specifically formulated for use within the rail industry.

Can be used with or without water softening equipment.

- Highly concentrated and very economical in use.

## TYPICAL APPLICATIONS

- Suitable for cleaning locomotives, carriages, freight wagons, tankers, trams and underground trains.
- An excellent fallout remover which will remove iron deposits from vehicle paintwork, window frames, and cladding.
- May be used for manual cleaning or via automatic washing plants.

## APPLICATION INSTRUCTIONS

For automated wash plants use in accordance with manufacturers instructions. Dilution will vary depending upon degree of soiling typically Oxalwash is used at a 1:40 dilution. For light soiling Oxalwash may be diluted at up to 1:100, for heavy deposits use at 1:30. Allow a short contact time, agitate and rinse with clean water. Oxalwash may also be applied via brush, swab or pressure washer.

# OXALWASH

Train exterior wash optimised for removal of iron staining



## TECHNICAL DATA

APPEARANCE	Slightly Viscous Liquid
COLOUR	Brown to Straw
ODOUR	Mild acidic
SOLUBILITY	Soluble in water
RELATIVE DENSITY	1.05 @ 20 °c
pH (concentrate)	1-2
PACK SIZES	1000, 210 and 20 litres

## PRECAUTIONS

Avoid spilling, skin and eye contact. Wear appropriate impervious protective clothing and eye protection when washing rolling stock.

## ACCREDITATIONS & REGISTRATIONS

Scientifics Approved

4Rail Approved

Rail Cat No: 007/007331: 20 litre  
Rail Cat No: 007/007316: 210 litre  
Rail Cat No: 007/007317: 1000 litre IBC

## STORAGE PRECAUTIONS

Keep containers tightly closed. Store at moderate temperatures in dry, well ventilated area.

## HEALTH AND SAFETY

Health and Safety Data sheet available separately.

## RELATED PRODUCTS



### THICKENED OXALWASH

A ready to use thickened version of Oxalwash to provide increased contact time on heavy deposits



### ECOWASH AUTOSHINE

Frequent use train exterior wash



### TRAILERWASH

Powerful soil remover and degreaser



ISO 14001:2004  
Cert No. 1263



OHS 536783



Q 05320

