

FASTKLEAN

Powerful fast drying degreaser



FASTKLEAN is used where the fastest-possible, unassisted drying after cleaning is essential. Fastklean's exceptional solvency provides the most effective penetration and softening of the most stubborn soils and coatings; adhesives, lacquers and paint films. Fastklean's solvent purity also ensures surfaces are left free of any residues, ensuring that adhesion of subsequent adhesive, paint or other coatings is not impaired.

ADVANTAGES

Removes even the heaviest oil and grease residues from metals, machinery and electrical components

Dries rapidly to a residue free finish

Contains no aromatic hydrocarbons

Flash point <0°C

Ideally suited for all manufacturing and maintenance environments

Aerosol incorporates pbca technology (compressed air propellant) helping to reduce your environmental impact

TYPICAL APPLICATIONS

- **Manufacturing** – Cleaning hardened oil and grease from machinery and preparing surfaces for painting
- **Auto-Repair** - Cleaning brake assemblies, carburettors and prior to painting

APPLICATION INSTRUCTIONS

1. (Before cleaning electrical equipment) switch off electrical supply.
2. Apply by brush or spray to the surface.
3. Allow to penetrate and dissolve grease.
4. Brush or wipe away residues and allow to air dry.

FASTKLEAN

Powerful fast drying degreaser



TECHNICAL DATA

APPEARANCE	Liquid
COLOUR	Colourless
ODOUR	Odour of alcohol
SOLUBILITY	Partially miscible with water
RELATIVE DENSITY	0.74
FLASH POINT (°C)	<0 CC (Closed cup)
VOC CONTENT	744 g/L
PACK SIZE	5 litre, 20 litre, 500ml aerosol

PRECAUTIONS

Keep away from heat, sparks and open flame. Provide good ventilation. Avoid contact with eyes.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry and cool place. Do not store near heat sources or expose to high temperatures.

HEALTH AND SAFETY

Health and Safety Data sheet available separately.

RELATED PRODUCTS



SUPERSOLVE AS

Electronic cleaner for critical surfaces



LOTOXANE®

Safe high flash point degreaser



QED

Quick dry electrical & workshop degreaser



ISO 14001:2004
Cert No. 1263



OHS 536783



Q 05320



Cert: 310314001